



Corestone Nature: Recreating the look of microcement without the environmental impact of cement. Exceptionally strong and scratch resistant.

APPLICATION TIME: 3 DAYS

Subfloor preparation may add to this time

GUARANTEE: 6 YEARS

Durable, scratch- and wear-resistant

TYPICAL THICKNESS: 3 MM

PROPERTIES

- Natural slip resistance
- Solvent-free and water based
 - Easy to maintain
 - Naturally durable
- Breathable for humid subfloors
 - BREEAM rated
- **System EPD available**

TYPICAL DATA

Layers	3-5
Elasticity	N/A
Shore Hardness	D85
Abrasion Resistance	Excellent
Fire Classification	B _{fl} -s1

Area Use Classification	23/33 - EN685
Slip Rating	R9/R10/R11 EN 51130
Resistance to Chair Castors	Excellent - EN 425
FeRFA Type	Type 8 - BS 8204



Corestone Nature Typical Section



Typical System Build Up Corestone Nature

• Penetrator	- Corestone Penetrator AQ	- 0.15 - 0.25 kg/m ²
• Primer/Scratch Coat	- EPI Primer / Scratchcoat 400 POX-NF	- 0.7 - 1.5 kg/m ²
• Body Coat	- Corestone Nature SL	- 4.5 - 5.0 kg/m ²
• Seal Coats	- Corestone Sealcoat T-mat	- 2 x 0.06 - 0.08 kg/m ²